



Wire products



Products range

Welded meshes

Mesh type	Diameter of bars		Distance between bars		Weight (kg/m ²)	Weight (kg/piece)	Length (m)	Meshes per package (piece)	Package weight (t)
	Longitudinal	Transversal	Longitudinal	Transversal					
Q 131	5	5	150	150	2.102	27.114	6	50	1.4
Q 188	6	6	150	150	3.027	39.044	6	50	2.0
Q 196	5	5	100	100	3.117	40.209	6	50	2.0
Q 257	7	7	150	150	4.120	53.143	6	50	2.7
Q 283	6	6	100	100	4.488	57.905	6	50	2.9
Q 295	7.5	7.5	150	150	4.729	61.006	6	50	3.1
Q 335	8	8	150	150	5.381	69.411	6	50	3.5
Q 385	7	7	100	100	6.109	78.809	6	25	2.0
Q 424	9	9	150	150	6.810	87.849	6	25	2.2
Q 503	8	8	100	100	7.979	102.934	6	25	2.6
Q 525	10	10	150	150	8.407	108.456	6	25	2.7
Q 636	9	9	100	100	10.099	130.276	6	20	2.6
Q 785	10	10	100	100	12.468	160.834	6	20	3.2

Lattice girders

Girder mark	Height (mm)	Zig-zag step	Wire diameter (mm)		
			Lower belt	Upper belt	Spiral
TPS	90 - 300	200	7 - 8	7 - 8	4.2 - 5

Cold Ribbed Wire Rod

Dia	Coil Weight	Inner dia	Outer dia	Length	Standard
6, 8, 10	2.5 MT	1.000 mm	1.500 mm	1.000 mm	B500A

Standards and grades of steel

Wire products are produced in quality B 500A according to EN 10080 - 2005 and EN 10080 - 1999